



THIS DRAWING IS THE PROPERTY OF VICTOR INSULATORS, INC. AND CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION WHICH MUST NOT BE DUPLICATED, USED, OR DISCLOSED OTHER THAN AS EXPRESSLY AUTHORIZED BY VICTOR INSULATORS, INC.

**DIMENSIONS**

DRY ARCING DISTANCE mm 284

**MECHANICAL VALUES**

SPECIFIED TENSILE LOAD(STL) kN 100

**ELECTRICAL VALUES**

RATED VOLTAGE kV 11  
 LOW FREQUENCY FLASHOVER, DRY kV 120  
 LOW FREQUENCY FLASHOVER, WET kV 65  
 IMPULSE FLASHOVER, POSITIVE kV 110

**PACKING INFORMATION**

NET WEIGHT kg 6

**APPROVED**  
 By A. E. Schwalm at 7:33 pm, Nov 13, 2023

	DATE	11-13-23	TM
SYSTEM VOLTAGE: 11 kV			
GUY STRAIN			
G100-TT-466-284-AA			
 <b>Victor Insulators, Inc.</b> 280 Maple Avenue Victor, New York, 14564 Telephone: (585)924-2127 www.victorinsulators.com			

FILE: G100-TT-466-284-AA