



DIMENSIONS

LEAKAGE DISTANCE	mm	3,590
DRY ARCING DISTANCE	mm	1,250

MECHANICAL VALUES

SPECIFIED CANTILEVER LOAD(SCL)	kN	13.5
MAX DESIGN CANTILEVER LOAD(MDCL)	kN	6.75

ELECTRICAL VALUES

RATED VOLTAGE	kV	161
LOW FREQUENCY FLASHOVER, DRY	kV	425
LOW FREQUENCY FLASHOVER, WET	kV	485
IMPULSE FLASHOVER, POSITIVE	kV	735
IMPULSE FLASHOVER, NEGATIVE	kV	840

PACKING INFORMATION

NET WEIGHT	kg	39.4
------------	----	------

APPROVED
By A. E. Schwalm at 7:48 am, Jan 11, 2024

DATE	01-10-24	TM
SYSTEM VOLTAGE: 161 kV		
LINE POST		
HP-70DA-1478-3590-XX		
	Victor Insulators, Inc.	
	280 Maple Avenue	
	Victor, New York, 14564	
	Telephone: (585)924-2127	
www.victorinsulators.com		

THIS DRAWING IS THE PROPERTY OF VICTOR INSULATORS, INC. AND CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION WHICH MUST NOT BE DUPLICATED, USED, OR DISCLOSED OTHER THAN AS EXPRESSLY AUTHORIZED BY VICTOR INSULATORS, INC.

FILE: HP-70DA-1478-3590-XX